

Material Safety Data Sheet

Prepared by Chem Alert

Product Name FILLCOAT

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier Name SUPERIOR COATINGS AUSTRALIA
Address Factory 14, 8-9 Gabrielle Court, Bayswater North Victoria, 3153, AUSTRALIA
Telephone + 61 3 9761 7331
Fax + 61 3 9761 7337
Emergency + 61 3 9761 7331

Synonyms FILL COAT, FILLCOAT.

Uses PAINT.

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA
CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

Risk And Safety Phrases Risk and Safety Phrases are standardised phrases allocated to Hazardous Substances. Risk phrases convey a general description of the physicochemical, environmental and health hazards of a substance. Safety phrases provide information on safe storage, handling, disposal, personal protection and first aid.

RISK PHRASES

R10 Flammable.
 R36 Irritating to eyes.

SAFETY PHRASES

S23 Do not breathe gas/fumes/vapour/spray (where applicable).
 S25 Avoid contact with eyes.
 S26 In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre.
 S43 In case of fire use only the recommended extinguishing agents.
 S51 Use only in well ventilated areas.
 S56 Dispose of this material and its container at hazardous or special waste collection point.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	Conc.	CAS No.
HYDROTREATED HEAVY NAPHTHA (PETROLEUM)		5 - 10%	64742-48-9
2-AMINO-2-METHYL-1-PROPANOL	C4-H11-N-O	1 - 2.5%	124-68-5
NAPHTHA, PETROLEUM HEAVY ALKYLATE		10 - 25%	64741-65-7
PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	C6-H12-O3	10 - 25%	108-65-6
ZINC STEARATE	C36-H70-O4.Zn	2.5 - 5%	557-05-1
1-METHOXY-2-PROPANOL	C4-H10-O2	2.5 - 5%	107-98-2
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)		1 - 2.5%	64742-49-0

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes.

**Colour
Rating
AMBER**

Material Safety Data Sheet

Prepared by Chem Alert

Product Name **FILLCOAT**

4. FIRST AID MEASURES cont.

- Inhalation** If swallowed or inhaled, remove from contaminated area. Apply artificial respiration if not breathing. Do not give direct mouth-to-mouth resuscitation. To protect rescuer, use air-viva, oxy-viva or one-way mask. Resuscitate in a well-ventilated area.
- Skin** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.
- Ingestion** For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor. If swallowed, do not induce vomiting.
- Advice To Doctor** Treat symptomatically.

5. FIRE FIGHTING MEASURES

- Flammability** Flammable. May evolve toxic gases (hydrocarbons, carbon oxides) when heated to decomposition. Eliminate all ignition sources including cigarettes, open flames, spark producing switches/tools, pilot lights, heaters, naked lights, mobile phones etc. when handling. Earth containers when dispensing fluids.
- Fire and Explosion** Flammable - explosive vapour. Evacuate area & contact emergency services. Toxic gases (carbon oxides, hydrocarbons) may be evolved when heated. Remain upwind and notify those downwind of hazard. Wear full protective equipment (see spill above) including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
- Extinguishing** Dry agent, carbon dioxide or foam. Prevent contamination of drains or waterways. Absorb runoff with sand or similar.
- Hazchem Code** 3[Y]

6. ACCIDENTAL RELEASE MEASURES

- Spillage** If spilt (bulk), contact emergency services. Wear splash-proof goggles, PVA/viton gloves, a Type A (Organic vapour) respirator or Air-line respirator, coveralls and rubber boots. Ventilate and clear area of all unprotected personnel. Eliminate heat and ignition sources, absorb spill with sand or similar and place in sealable containers for disposal. Prevent spill entering drains or waterways.

7. HANDLING AND STORAGE

- Handling** Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas (eg. if container is damaged).
- Storage** Store in cool, dry, well ventilated area, preferably flammables store, removed from direct sunlight, heat and ignition sources, oxidising agents (eg. peroxides), acids (eg. nitric acid) and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should have appropriate fire protection and ventilation systems.

Colour
Rating
AMBER

Material Safety Data Sheet

Prepared by Chem Alert

Product Name FILLCOAT

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ventilation Do not inhale vapours. Use in well ventilated areas. In poorly ventilated areas, mechanical explosion proof extraction ventilation is recommended. Flammable/explosive vapours may accumulate in poorly ventilated areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

Exposure Standards

HYDROTREATED HEAVY NAPHTHA (PETROLEUM) (64742-48-9)
ES-STEL : 400 ppm (1800 mg/m³)

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (108-65-6)
ES-TWA : 50 ppm (274 mg/m³) Propylene glycol monomethyl ether acetate
ES-STEL : 150 ppm (822 mg/m³)

ZINC STEARATE (557-05-1)
ES-TWA : 10 mg/m³ (Stearates)

1-METHOXY-2-PROPANOL (107-98-2)
ES-TWA : 100 ppm (369 mg/m³)
ES-STEL : 150 ppm (553 mg/m³)
WES-TWA : 100 ppm (369 mg/m³)

PPE Wear coveralls, splash-proof goggles and PVA or viton (R) gloves. Where an inhalation risk exists, wear a Type A (Organic vapour) Respirator. If spraying, wear a Type A-Class P1 (Organic vapour and Particulate) Respirator or an Air-line respirator. If sanding dry product, wear a Class P1 (Particulate) Respirator.



9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: LIQUID
Odour: HYDROCARBON ODOUR
pH: NOT AVAILABLE
Vapour Pressure: 0.7 kPa
Vapour Density: NOT AVAILABLE
Boiling Point: > 160 C
Melting Point: -20 C
Evaporation Rate: NOT AVAILABLE
Solubility (water): INSOLUBLE
Specific Gravity: 1.03 - 1.06
% Volatiles: NOT AVAILABLE
Flammability: FLAMMABLE
Flash Point: 40 C
Upper Explosion Limit: NOT AVAILABLE
Lower Explosion Limit: NOT AVAILABLE
Autoignition Temperature: 250 C

**Colour
Rating
AMBER**

Material Safety Data Sheet

Prepared by Chem Alert

Product Name **FILLCOAT**

10. STABILITY AND REACTIVITY

Reactivity Incompatible with oxidising agents (eg. hypochlorites, peroxides), acids (eg. sulfuric acid), heat and ignition sources.

Decomposition Products May evolve toxic gases (hydrocarbons, carbon oxides) when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Health Hazard Summary Moderate toxicity - irritant. This product has the potential to cause adverse health effects with over exposure. Use safe work practices to avoid eye or skin contact and vapour generation - inhalation. Chronic exposure to organic solvents may cause liver, kidney and central nervous system damage.

Eye Irritant. Exposure may result in lacrimation, irritation, pain, redness, conjunctivitis and possible corneal burns with prolonged contact.

Inhalation Moderate toxicity. Inhalation may result in mucous membrane irritation of the nose and throat, nausea and dizziness. Over exposure may cause breathing difficulties and unconsciousness.

Skin Irritant. Prolonged contact may result in drying and defatting of the skin, rash and dermatitis. Toxic effects may result from skin absorption.

Ingestion Moderate toxicity. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness, drowsiness and unconsciousness with large doses. Aspiration may result in chemical pneumonitis and pulmonary oedema.

Toxicity Data 2-AMINO-2-METHYL-1-PROPANOL (124-68-5)
LD50 (Ingestion) : 2150 mg/kg (mouse)

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE (108-65-6)
LD50 (Skin) : > 5000 mg/kg (rabbit)
LD50 (Ingestion) : 8532 mg/kg (rat)

1-METHOXY-2-PROPANOL (107-98-2)
LC50 (Inhalation) : 10000 ppm/5 hours (rat)
LD50 (Skin) : 13000 mg/kg (rabbit)
LD50 (Ingestion) : 5000 mg/kg (dog)

12. ECOLOGICAL INFORMATION

Environment Aliphatic hydrocarbons behave differently in the environment depending on their size. WATER: Light aliphatics volatilise rapidly from water (half life - few hours). Bioconcentration should not be significant. SOIL: Light aliphatics biodegrade quickly in soil and water, heavy aliphatics biodegrade very slowly. ATMOSPHERE: Vapour-phase aliphatics will degrade by reaction with hydroxyl radicals.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Wearing the protective equipment outlined, ensure all ignition sources are extinguished. For small quantities, absorb on paper, sand or similar and evaporate under a fume cupboard or open area. For large volumes, atomise into incinerator (mixing with more flammable solvent if required) or recycle by gravimetric separation, distilling & reusing. Contact the manufacturer for additional information if required.

Colour
Rating
AMBER

Material Safety Data Sheet

Prepared by Chem Alert

Product Name **FILLCOAT**

13. DISPOSAL CONSIDERATIONS cont.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

Transport Class 3 Flammable liquid. Do not transport with chemicals of class; 1 (Explosives), 2.1/ 2.3 (Flammable/ Toxic gases), 4.2 (Spontaneously combustibles), 5.1 (Oxidising agents), 5.2 (Organic peroxides), 6 (Toxics), 7 (Radioactives) and foodstuffs.

UN Number 1263

Shipping Name PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

DG Class 3

Subsidiary Risk(s) None Allocated

Packing Group III

Hazchem Code 3[Y]

IMDG

UN Number 1263

DG Class 3

Subsidiary Risk(s) None Allocated

Packing Group III

IATA

UN Number 1263

DG Class 3

Subsidiary Risk(s) None Allocated

Packing Group III

Inhalation None Allocated

Packing Group

15. REGULATORY INFORMATION

AICS All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

Poison Schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

16. OTHER INFORMATION

Additional Information WELDING - SANDING - CUTTING DRIED OR CURED PRODUCT: If sanding, cutting or welding dried or cured product, adverse health effects may be avoided by the use of appropriate engineering controls and/or personal protective equipment. If welding, wear a Class P2 (Metal fume) respirator and depending on the nature of the surface being welded, additional protection (eg. for organic vapours/acid gas) may also be required. A Class P1 (Particulate)

Colour Rating
AMBER

Material Safety Data Sheet

Prepared by Chem Alert

Product Name **FILLCOAT**

16. OTHER INFORMATION cont.

respirator is recommended if dust is generated.

WORK PRACTICES - SOLVENTS: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGE (TWA) or WES (WORKPLACE EXPOSURE STANDARD) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

COLOUR RATING SYSTEM: Chem Alert reports are assigned a colour rating of Green, Amber or Red for the purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all Chem Alert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

ABBREVIATIONS:

mg/m³ - Milligrams per cubic metre

ppm - Parts Per Million

TWA/ES - Time Weighted Average or Exposure Standard.

CNS - Central Nervous System

NOS - Not Otherwise Specified

pH - relates to hydrogen ion concentration - this value will relate to a scale of 0 - 14, where 0 is highly acidic and 14 is highly alkaline.

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

M - moles per litre, a unit of concentration.

IARC - International Agency for Research on Cancer.

Report Reviewed 25th January 2006

Date Printed 25th January 2006

**Colour
Rating
AMBER**

Material Safety Data Sheet

Prepared by Chem Alert

Product Name FILLCOAT

16. OTHER INFORMATION cont.

Report Status Chem Alert reports are compiled as an independent source of information by RMT's scientific department. The information is based on the latest chemical and toxicological research, and in compliance with relevant standards, guidance notes and legislation (where applicable). The Chem Alert report is not intended as a replacement to the manufacturer's original MSDS that is provided to Chem Alert subscribers for convenience. In many instances, Chem Alert reports are compiled on behalf of manufacturers, in which case they serve as the "Manufacturer's MSDS" and are clearly identified as such on the relevant reports.

Prepared By Risk Management Technologies
5 Ventnor Avenue, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Web: www.rmt.com.au

**Colour
Rating
AMBER**